



ANR020 PROTEUS-III

REMOTE GPIO CONTROL - HOW TO

VERSION 1.0

JULY 10, 2020

Revision history

Manual version	Notes	Date
1.0	• Initial version	July 2020

Abbreviations and abstract

Abbreviation	Name	Description
CS	Checksum	Byte wise XOR combination of the preceding fields.
I/O	Input/output	Pinout description.
Payload		The intended message in a frame / package.
RF	Radio frequency	Describes wireless transmission.
UART	Universal Asynchronous Receiver Transmitter	Allows the serial communication with the module.
[HEX] 0xhh	Hexadecimal	All numbers beginning with 0x are hexadecimal numbers. All other numbers are decimal, unless stated otherwise.

Contents

1	Introduction	4
1.1	Supported GPIOs	4
2	General description	5
2.1	Remote GPIO configuration	5
2.1.1	Local GPIO configuration	7
2.2	Remote control	9
2.2.1	Local control	10
3	Examples	11
3.1	Example 1: Control "Module 1" by "Module 2"	11
3.1.1	Boot-up and connection setup	12
3.1.2	Configure and control a GPIO as output	13
3.1.3	Configure and control a GPIO as input	14
3.2	Example 2: Control "Module 1" by smart phone	16
3.2.1	Boot-up and connection setup	16
3.2.2	Configure and control a GPIO as output	18
3.2.3	Configure and control a GPIO as input	22
4	Important notes	27
4.1	General customer responsibility	27
4.2	Customer responsibility related to specific, in particular safety-relevant applications	27
4.3	Best care and attention	27
4.4	Customer support for product specifications	27
4.5	Product improvements	28
4.6	Product life cycle	28
4.7	Property rights	28
4.8	General terms and conditions	28
5	Legal notice	29
5.1	Exclusion of liability	29
5.2	Suitability in customer applications	29
5.3	Trademarks	29
5.4	Usage restriction	29
6	License terms	31
6.1	Limited license	31
6.2	Usage and obligations	31
6.3	Ownership	32
6.4	Firmware update(s)	32
6.5	Disclaimer of warranty	32
6.6	Limitation of liability	33
6.7	Applicable law and jurisdiction	33
6.8	Severability clause	33
6.9	Miscellaneous	33

1 Introduction

The Proteus-III is a Bluetooth® LE module based on the nRF52 Nordic Semiconductors SoC which presents various Bluetooth® LE and low power features. It provides a command based UART interface that allows the configuration and control of the Proteus-III by simple commands. Besides the commands needed for configuration and radio data transmission, various commands are provided to use the so called remote GPIO feature.

This feature allows to write and read up to 6 GPIOs of the Proteus-III via Bluetooth® LE connection. With help of this, simple applications, like switches or digital level detectors, can be realized with the Proteus-III without the need of connecting a host controller to it.


This application note describes which steps have to be run to switch a GPIO and how to read the pin level of a GPIO via remote connection. First or all a general description follows, then in the `Examples` section it is demonstrated how the GPIOs can be controlled by a second Proteus-III radio module or by smart phone.

1.1 Supported GPIOs

The supported GPIOs are identified by so called GPIO_IDs, that are used in the commands for GPIO control. The following GPIOs of the Proteus-III are supported for remote and local access.

No	GPIO_ID	Supported functions
B1	1	Input, Output
B2	2	Input, Output
B3	3	Input, Output
B4	4	Input, Output
B5	5	Input, Output
B6	6	Input, Output

Table 1: Supported GPIO_IDs



2 General description

This chapter is based on a test setup with two Proteus-III radio modules. "Module 1" is the one, whose GPIOs are configured and controlled. It can be run without host controller. "Module 2" is the remote device which sends the commands for GPIO control via radio to "Module 1". It must be controlled via host controller "Host 2" to send the correct commands. Instead of the remote Proteus-III "Module 2", another remote device such as a smart phone can also be used.

Chapter 3.1 contains an example, where the Proteus-III "Module 1" is controlled by another Proteus-III "Module 2". Chapter 3.2 shows the example, where the Proteus-III "Module 1" is controlled by a smart phone.



The full description of the necessary UART commands can be found in the Proteus-III manual, where the radio commands are described in detail in the application note "ANR009 Proteus-III Advanced Developer Guide".

2.1 Remote GPIO configuration

To use the remote GPIO control feature of the Proteus-III "Module 1", the GPIOs of interest must be configured first. This configuration defines the GPIO function of the pin. Either an output pin, or an input pin with/without pull resistor.

To do so, the remote device "Module 2" must setup a Bluetooth® LE connection to the radio module "Module 1" and send a `CMD_GPIO_REMOTE_WRITECONFIG_REQ` command via Bluetooth® LE thereafter (see figure 1).

The configuration is stored in flash memory, such that it is retained even after a device restart.

It can be read back by the remote device "Module 2" using the `CMD_GPIO_REMOTE_READCONFIG_REQ` command (see figure 2).

After the configuration has been done, the configured GPIOs are ready to be controlled.




Figure 1: Configure the local GPIOs via remote device host




Figure 2: Read the configuration of the local GPIOs via remote device host

2.1.1 Local GPIO configuration



In case no host controller is connected to "Module 1", please go to the next chapter Remote control.

In case a host controller is connected to "Module 1", both, writing and reading the GPIO configuration can be done locally using the commands `CMD_GPIO_LOCAL_WRITECONFIG_REQ` and `CMD_GPIO_LOCAL_READCONFIG_REQ` (see figure 3 and figure 4). In this case, the host controller of "Module 1" must send the respective commands via UART to the "Module 1".




Figure 3: Configure the local GPIOs via local host




Figure 4: Read the configuration of the local GPIOs via local host

2.2 Remote control

To control a GPIO via remote device, first setup a Bluetooth® LE connection to the radio module "Module 1" and send the respective commands, `CMD_GPIO_REMOTE_WRITE_REQ` for setting GPIO output values (see figure 5), or `CMD_GPIO_REMOTE_READ_REQ` for reading GPIO values (see figure 6).

In case a host controller is connected to "Module 1", each time the GPIOs are written to via remote connection, the local host is informed using a `CMD_GPIO_REMOTE_WRITE_IND` message.




Figure 5: Set the output value of a GPIO via remote device




Figure 6: Read the input value of a GPIO via remote device

2.2.1 Local control

In case a host controller is connected to "Module 1", it also can write and read the GPIO status of the radio module "Module 1". To do so, the host controller must send the respective commands, `CMD_GPIO_LOCAL_WRITE_REQ` to set GPIO output values (see figure 7), or `CMD_GPIO_LOCAL_READ_REQ` to read GPIO values (see figure 8). Each time the GPIOs are written to via local host, the connected remote device is informed using a `CMD_GPIO_LOCAL_WRITE_IND` message.




Figure 7: Set the output value of a GPIO via host controller




Figure 8: Read the input value of a GPIO via host controller

3 Examples



The below commands are in hexadecimal notation. The arrow in the left column describes, whether it's a message from host to radio module, or vice versa. A request command is always sent from host to module (\Rightarrow). An indication, confirmation or response message is always sent from module to host (\Leftarrow).

3.1 Example 1: Control "Module 1" by "Module 2"

This chapter describes how to setup a Bluetooth® LE connection between two Proteus-III radio modules, and how to configure and control the GPIOs of one of both modules via Bluetooth® LE connection.

The setup is as shown above, where "Module 1" is the one, whose GPIOs are switched via radio. It can run without host controller. "Module 2" is the one which must be connected to a host controller "Host 2", to send the corresponding configuration and control commands.

For demonstration purposes, two Proteus-III evaluation boards are appropriate. As "host" a Windows computer including the terminal program *hterm* can be taken. The USB connector of the Proteus-III evaluation board allows an easy connection to the Windows computer.




Figure 9: The terminal program hterm

Hint: Please note that the Würth Elektronik eiSos's tool Smart Commander (version 1.0.1.0 or newer) also includes the function to control the GPIOs of the Proteus-III. This tool allows

to generate the commands, that are shown below, by clicking the corresponding buttons in the Smart Commander GUI menu. This tool will be not used in this example.




Figure 10: The Würth Elektronik eiSos's tool Smart Commander

3.1.1 Boot-up and connection setup

1. Power-up the modules and make their UARTs accessible by the host(s) (115200 Baud, 8n1). After the power-up or after reset the following sequence is sent from the module to the host.

Info	Module 1	Module 2
← Response CMD_GETSTATE_CNF: Module 1 started in ACTION_IDLE mode.	02 41 02 00 01 01 41	
← Response CMD_GETSTATE_CNF: Module 2 started in ACTION_IDLE mode.		02 41 02 00 01 01 41

2. Request the MAC address FS_BTMAC of both modules.

Info	Module 1	Module 2
⇒ Request CMD_GET_REQ with settings index 4		02 10 01 00 04 17
← Response CMD_GET_CNF: FS_BTMAC of Module 2 is 0x55 0x00 0x00 0xDA 0x18 0x00		02 50 07 00 00 55 00 00 DA 18 00 C2
⇒ Request CMD_GET_REQ with settings index 4	02 10 01 00 04 17	
← Response CMD_GET_CNF: FS_BTMAC of Module 1 is 0x11 0x00 0x00 0xDA 0x18 0x00	02 50 07 00 00 11 00 00 DA 18 00 86	

3. Connect Module 2 to Module 1 via Bluetooth®.

Info	Module 1	Module 2
⇒ Request CMD_CONNECT_REQ with FS_BTMAC of Module 1		02 06 06 00 11 00 00 DA 18 00 D1
⇐ Response CMD_CONNECT_CNF: Request understood, try to connect now		02 46 01 00 00 45
⇐ Indication CMD_CONNECT_IND: Physical connection established successfully to module with FS_BTMAC 0x11 0x00 0x00 0xDA 0x18 0x00		02 86 07 00 00 11 00 00 DA 18 00 50
⇐ Indication CMD_CONNECT_IND: Physical connection established successfully to module with FS_BTMAC 0x55 0x00 0x00 0xDA 0x18 0x00	02 86 07 00 00 55 00 00 DA 18 00 14	
⇐ Indication CMD_CHANNELOPEN_RSP: Channel opened successfully to module with FS_BTMAC 0x11 0x00 0x00 0xDA 0x18 0x00 and maximum payload size of 0xF3 (243 Bytes) per packet		02 C6 08 00 00 11 00 00 DA 18 00 F3 E3
⇐ Indication CMD_CHANNELOPEN_RSP: Channel opened successfully to module with FS_BTMAC 0x55 0x00 0x00 0xDA 0x18 0x00 and maximum payload size of 0xF3 (243 Bytes) per packet	02 C6 08 00 00 55 00 00 DA 18 00 F3 A7	

- Now the Bluetooth® LE connection is open, and the configuration and control of the GPIOs of "Module 1" can be done.

3.1.2 Configure and control a GPIO as output

If the Bluetooth® LE connection has been setup, as shown in chapter 3.1.1, the following steps can be run to configure the GPIO *B1* with GPIO_ID 1 as output pin.

- First of all configure the GPIO *B1* with GPIO_ID 1 as output pin with default level LOW.

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_WRITECONFIG_REQ: Configure GPIO <i>B1</i> (GPIO_ID 1) as output with default level LOW		02 28 04 00 03 01 02 00 2E
⇐ Response CMD_GPIO_REMOTE_WRITECONFIG_CNF: GPIO with GPIO_ID 1 has been configured successfully		02 68 04 00 00 02 01 00 6D
⇐ Indication CMD_GPIO_REMOTE_WRITECONFIG_IND: GPIO with GPIO_ID 1 has been configured to output LOW by remote device	02 A8 04 00 03 01 02 00 AE	

- Read the current configuration

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_READCONFIG_REQ:		02 2C 00 00 2E
⇐ Response CMD_GPIO_REMOTE_READCONFIG_CNF: GPIO with GPIO_ID 1 has been configured to output LOW, GPIO_ID 2 - 6 are not configured		02 6C 14 00 00 03 01 02 00 02 02 00 02 03 00 02 04 00 02 05 00 02 06 00 7E

3. Switch the GPIO B1 with GPIO_ID 1 to HIGH.

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_WRITE_REQ: Set the GPIO B1 (GPIO_ID 1) to HIGH		02 29 03 00 02 01 01 2A
⇐ Response CMD_GPIO_REMOTE_WRITE_CNF: GPIO with GPIO_ID 1 has been successfully		02 69 04 00 00 02 01 00 6C
⇐ Indication CMD_GPIO_REMOTE_WRITE_IND: GPIO with GPIO_ID 1 has been set to HIGH by remote device	02 A9 03 00 02 01 01 AA	

4. Read the current state of the GPIO B1 with GPIO_ID 1.

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_READ_REQ: Read the state of GPIO B1 (GPIO_ID 1)		02 2A 02 00 01 01 2A
⇐ Response CMD_GPIO_REMOTE_READ_CNF: GPIO with GPIO_ID 1 is HIGH		02 6A 04 00 00 02 01 01 6E

5. Switch the GPIO B1 with GPIO_ID 1 again to LOW.

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_WRITE_REQ: Set the GPIO B1 (GPIO_ID 1) to LOW		02 29 03 00 02 01 00 2B
⇐ Response CMD_GPIO_REMOTE_WRITE_CNF: GPIO with GPIO_ID 1 has been set successfully		02 69 04 00 00 02 01 00 6C
⇐ Indication CMD_GPIO_REMOTE_WRITE_IND: GPIO with GPIO_ID 1 has been set to LOW by the remote device	02 A9 03 00 02 01 00 AB	

3.1.3 Configure and control a GPIO as input

If the Bluetooth® LE connection has been setup, as shown in chapter 3.1.1, the following steps can be run to configure the GPIO B1 with GPIO_ID 1 as input pin.

1. First of all configure the GPIO B1 with GPIO_ID 1 as input pin with default level LOW.

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_WRITECONFIG_REQ: Configure GPIO B1 (GPIO_ID 1) as input with pull down resistor		02 28 04 00 03 01 01 01 2C
⇐ Response CMD_GPIO_REMOTE_WRITECONFIG_CNF: GPIO with GPIO_ID 1 has been configured successfully		02 68 04 00 00 02 01 00 6D
⇐ Indication CMD_GPIO_REMOTE_WRITECONFIG_IND: GPIO with GPIO_ID 1 has been configured to input with pull down resistor by the remote device	02 A8 04 00 03 01 01 01 AE	

2. Read the current configuration

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_READCONFIG_REQ:		02 2C 00 00 2E
⇐ Response CMD_GPIO_REMOTE_READCONFIG_CNF: GPIO with GPIO_ID 1 has been configured to input with pulldown, GPIO_ID 2 - 6 are not configured		02 6C 14 00 00 03 01 01 01 02 02 00 02 03 00 02 04 00 02 05 00 02 06 00 7C

3. Leave the GPIO B1 open and read the current state of the GPIO B1 with GPIO_ID 1.

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_READ_REQ: Read the state of GPIO B1 (GPIO_ID 1)		02 2A 02 00 01 01 2A
⇐ Response CMD_GPIO_REMOTE_READ_CNF: GPIO with GPIO_ID 1 is LOW		02 6A 04 00 00 02 01 00 6F

4. Now, apply a HIGH signal to the GPIO B1 and read the current state of the GPIO B1 with GPIO_ID 1.

Info	Module 1	Module 2
⇒ Request CMD_GPIO_REMOTE_READ_REQ: Read the state of GPIO B1 (GPIO_ID 1)		02 2A 02 00 01 01 2A
⇐ Response CMD_GPIO_REMOTE_READ_CNF: GPIO with GPIO_ID 1 is HIGH		02 6A 04 00 00 02 01 01 6E

3.2 Example 2: Control "Module 1" by smart phone

This chapter describes how to setup a Bluetooth® LE connection between a smart phone and a Proteus-III radio module, and how to configure and control the GPIOs of the Proteus-III "Module 1" via the Bluetooth® LE connection.

"Module 1" itself can run without host controller as its GPIOs are controlled via radio. For demonstration purposes, we here again use a Proteus-III evaluation board, which is connected to a Windows computer including the terminal program *hterm*, which is the host "Host 1".




Figure 11: The terminal program hterm


Instead of "Module 2" we here use an Android smart phone including the app "Proteus Connect", which allows the operation with all radio modules from the Proteus series. Besides the functions for connection setup and data transmission, this app contains the functions of GPIO configuration and control, which we will focus on in this chapter.

3.2.1 Boot-up and connection setup


- Connect the Proteus evaluation board to a PC using an USB cable.
- Open a terminal program using the Proteus default UART settings (115200 Baud, 8n1).
- Press the reset button on the Proteus evaluation board. The Proteus module outputs a `CMD_GETSTATE_CNF` to indicate that it is ready for operation.

Info	Module 1
← Response CMD_GETSTATE_CNF: Module 1 started in ACTION_IDLE mode.	02 41 02 00 01 01 41

- Then open the "Proteus Connect" app and press "Scan". As soon as the Proteus-III appears in the scan list, click on it to start the connection setup.



- In the app a new window pops up, which shows the connection setup steps in its log window.



- On the radio module side, the Proteus-III outputs its connection setup related messages.


Info	Module 1
⇐ Indication CMD_CONNECT_IND: Physical connection established successfully to device with FS_BTMAC 0x55 0x00 0x00 0xDA 0x18 0x00	02 86 07 00 00 55 00 00 DA 18 00 14
⇐ Indication CMD_CHANNELOPEN_RSP: Channel opened successfully to device with FS_BTMAC 0x55 0x00 0x00 0xDA 0x18 0x00 and maximum payload size of 0xF3 (243 Bytes) per packet	02 C6 08 00 00 55 00 00 DA 18 00 F3 A7

- Now the Bluetooth® LE connection is open, and the configuration and control of the GPIOs of "Module 1" can be done.

3.2.2 Configure and control a GPIO as output

If the Bluetooth® LE connection has been setup, as shown in chapter 3.2.1, the following steps can be run to configure the GPIO *B1* with GPIO_ID 1 as output pin.

1. First of all configure the GPIO *B1* with GPIO_ID 1 as output pin with default level LOW. To do so, press the "..."-menu button and then "GPIO config" .



2. A menu opens, which allows the configuration of the GPIOs. First of all, press on the refresh button to read the current pin configuration of the radio module.




- Pressing this button sends a `CMD_GPIO_REMOTE_READCONFIG_REQ` message (02 2C) to the radio module, which responds with a `CMD_GPIO_REMOTE_READCONFIG_CNF` message (02 6C 02 01 00 02 02 00 02 03 00 02 04 00 02 05 00 02 06 00), which states that all pins with `GPIO_ID 1` to `6` are not configured.



Please note that the format of the radio commands differs from the format of the UART commands. The documentation of the radio command format for configuration and control of the GPIOs can be found in application note "ANR009 Proteus-III Advanced Developer Guide".


- Now select pin *B1* with output LOW in the app and press "CONFIG PIN".




5. Pressing this button sends a `CMD_GPIO_REMOTE_WRITECONFIG_REQ` message (02 28 03 01 02 00 / configure GPIO with **GPIO_ID 1** to **output LOW**) to the radio module, which responds with a `CMD_GPIO_REMOTE_WRITECONFIG_CNF` message (02 68 02 01 00 / configured GPIO with **GPIO_ID 1** successfully).
6. On the radio module side, the Proteus-III outputs the corresponding indication message

Info	Module 1
⇐ Indication <code>CMD_GPIO_REMOTE_WRITECONFIG_IND</code> : The GPIO with GPIO_ID 1 has been configured to output LOW by the remote device	02 A8 04 00 03 01 02 00 AE

7. Now, go to the sub menu "GPIO read/write" and press the refresh button to read all GPIO states.



8. Pressing this button sends a CMD_GPIO_REMOTE_READ_REQ message (02 2A 06 01 02 03 04 05 06 / request state of GPIO_ID 1 to 6) to the radio module, which responds with a CMD_GPIO_REMOTE_READ_CNF message (02 6A 02 01 00 02 02 FF 02 03 FF 02 04 FF 02 05 FF 02 06 FF), which states that the GPIO with GPIO_ID 1 is LOW, but the GPIOs with GPIO_ID 2 to 6 are not configured.
9. Next, press "B1", move the slider to HIGH and press "WRITE PIN" to set the GPIO with GPIO_ID 1 to HIGH.



10. Pressing these buttons sends a CMD_GPIO_REMOTE_WRITE_REQ message (02 29 02 01 01 / set the GPIO with GPIO_ID 1 to HIGH) to the radio module, which responds with

a CMD_GPIO_REMOTE_WRITE_CNF message (02 69 02 01 00), which states that the GPIO with GPIO_ID 1 has been set successfully.


- On the radio module side, the Proteus-III outputs the corresponding indication message

Info	Module 1
⇐ Indication CMD_GPIO_REMOTE_WRITE_IND: The GPIO with GPIO_ID 1 has been set to HIGH by the remote device	02 A9 03 00 02 01 01 AA


3.2.3 Configure and control a GPIO as input

If the Bluetooth® LE connection has been setup, as shown in chapter 3.2.1, the following steps can be run to configure the GPIO B1 with GPIO_ID 1 as input pin.

- First of all configure the GPIO B1 with GPIO_ID 1 as input pin with pull down resistor. To do so, press the "..."-menu button and then "GPIO config".



- A menu opens, which allows the configuration of the GPIOs. First of all, press on the refresh button to read the current pin configuration of the radio module.




- Pressing this button sends a `CMD_GPIO_REMOTE_READCONFIG_REQ` message (02 2C) to the radio module, which responds with a `CMD_GPIO_REMOTE_READCONFIG_CNF` message (02 6C 02 01 00 02 02 00 02 03 00 02 04 00 02 05 00 02 06 00), which states that all pins with `GPIO_ID 1` to `6` are not configured.



Please note that the format of the radio commands differs from the UART command format. The documentation of the radio command format for configuration and control of the GPIOs can be found in application note "ANR009 Proteus-III Advanced Developer Guide".


- Now select pin *B1* with input pull down in the app and press "CONFIG PIN".




5. Pressing this button sends a `CMD_GPIO_REMOTE_WRITECONFIG_REQ` message (02 28 03 01 01 01 / configured GPIO with **GPIO_ID 1** to **input pull down**) to the radio module, which responds with a `CMD_GPIO_REMOTE_WRITECONFIG_CNF` message (02 68 02 01 00 / configured GPIO with **GPIO_ID 1** successfully).
6. On the radio module side, the Proteus-III outputs the corresponding indication message

Info	Module 1
⇐ Indication <code>CMD_GPIO_REMOTE_WRITECONFIG_IND</code> : The GPIO with GPIO_ID 1 has been configured to input pull down by the remote device	02 A8 04 00 03 01 01 01 AC

7. Now, go to the sub menu "GPIO read/write" and press the refresh button to read all GPIO states.



8. Pressing this button sends a CMD_GPIO_REMOTE_READ_REQ message (02 2A 06 01 02 03 04 05 06 / request state of GPIO_ID 1 to 6) to the radio module, which responds with a CMD_GPIO_REMOTE_READ_CNF message (02 6A 02 01 00 02 02 FF 02 03 FF 02 04 FF 02 05 FF 02 06 FF), which states that the GPIO with GPIO_ID 1 is LOW, but the GPIOs with GPIO_ID 2 to 6 are not configured.
9. Apply a HIGH signal to the pin by connecting VCC to it. Then press "B1" and press "READ PIN" to read the GPIO with GPIO_ID 1.



10. Pressing these buttons sends a CMD_GPIO_REMOTE_READ_REQ message (02 2A 01 01 / read the GPIO with GPIO_ID 1) to the radio module, which responds with a

CMD_GPIO_REMOTE_READ_CNF message (02 6A 02 01 01), which states that the GPIO with GPIO_ID 1 is HIGH.

4 Important notes

The following conditions apply to all goods within the wireless connectivity product range of Würth Elektronik eiSos GmbH & Co. KG:

4.1 General customer responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact, it is up to the customer to evaluate, where appropriate to investigate and to decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not. Accordingly, the customer is cautioned to verify that the documentation is current before placing orders.

4.2 Customer responsibility related to specific, in particular safety-relevant applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. The same statement is valid for all software sourcecode and firmware parts contained in or used with or for products in the wireless connectivity and sensor product range of Würth Elektronik eiSos GmbH & Co. KG. In certain customer applications requiring a high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health, it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

4.3 Best care and attention

Any product-specific data sheets, manuals, application notes, PCN's, warnings and cautions must be strictly observed in the most recent versions and matching to the products firmware revisions. This documents can be downloaded from the product specific sections on the wireless connectivity homepage.

4.4 Customer support for product specifications

Some products within the product range may contain substances, which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case, the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

4.5 Product improvements

Due to constant product improvement, product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard, we inform about major changes. In case of further queries regarding the PCN, the field sales engineer, the internal sales person or the technical support team in charge should be contacted. The basic responsibility of the customer as per section 4.1 and 4.2 remains unaffected. All wireless connectivity module driver software "wireless connectivity SDK" and its source codes as well as all PC software tools are not subject to the Product Change Notification information process.

4.6 Product life cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this, we cannot ensure that all products within our product range will always be available. Therefore, it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

4.7 Property rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG. Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

4.8 General terms and conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

5 Legal notice

5.1 Exclusion of liability

Würth Elektronik eiSos GmbH & Co. KG considers the information in this document to be correct at the time of publication. However, Würth Elektronik eiSos GmbH & Co. KG reserves the right to modify the information such as technical specifications or functions of its products or discontinue the production of these products or the support of one of these products without any written announcement or notification to customers. The customer must make sure that the information used corresponds to the latest published information. Würth Elektronik eiSos GmbH & Co. KG does not assume any liability for the use of its products. Würth Elektronik eiSos GmbH & Co. KG does not grant licenses for its patent rights or for any other of its intellectual property rights or third-party rights.

Notwithstanding anything above, Würth Elektronik eiSos GmbH & Co. KG makes no representations and/or warranties of any kind for the provided information related to their accuracy, correctness, completeness, usage of the products and/or usability for customer applications. Information published by Würth Elektronik eiSos GmbH & Co. KG regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof.

5.2 Suitability in customer applications

The customer bears the responsibility for compliance of systems or units, in which Würth Elektronik eiSos GmbH & Co. KG products are integrated, with applicable legal regulations. Customer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of Würth Elektronik eiSos GmbH & Co. KG components in its applications, notwithstanding any applications-related information or support that may be provided by Würth Elektronik eiSos GmbH & Co. KG. Customer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences lessen the likelihood of failures that might cause harm and take appropriate remedial actions. The customer will fully indemnify Würth Elektronik eiSos GmbH & Co. KG and its representatives against any damages arising out of the use of any Würth Elektronik eiSos GmbH & Co. KG components in safety-critical applications.

5.3 Trademarks

AMBER wireless is a registered trademark of Würth Elektronik eiSos GmbH & Co. KG. All other trademarks, registered trademarks, and product names are the exclusive property of the respective owners.

5.4 Usage restriction

Würth Elektronik eiSos GmbH & Co. KG products have been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where

a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover, Würth Elektronik eiSos GmbH & Co. KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH & Co. KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component, which is used in electrical circuits that require high safety and reliability function or performance. By using Würth Elektronik eiSos GmbH & Co. KG products, the customer agrees to these terms and conditions.

6 License terms

This License Terms will take effect upon the purchase and usage of the Würth Elektronik eiSos GmbH & Co. KG wireless connectivity products. You hereby agree that this license terms is applicable to the product and the incorporated software, firmware and source codes (collectively, "Software") made available by Würth Elektronik eiSos in any form, including but not limited to binary, executable or source code form.

The software included in any Würth Elektronik eiSos wireless connectivity product is purchased to you on the condition that you accept the terms and conditions of this license terms. You agree to comply with all provisions under this license terms.

6.1 Limited license

Würth Elektronik eiSos hereby grants you a limited, non-exclusive, non-transferable and royalty-free license to use the software and under the conditions that will be set forth in this license terms. You are free to use the provided Software only in connection with one of the products from Würth Elektronik eiSos to the extent described in this license terms. You are entitled to change or alter the source code for the sole purpose of creating an application embedding the Würth Elektronik eiSos wireless connectivity product. The transfer of the source code to third parties is allowed to the sole extent that the source code is used by such third parties in connection with our product or another hardware provided by Würth Elektronik eiSos under strict adherence of this license terms. Würth Elektronik eiSos will not assume any liability for the usage of the incorporated software and the source code. You are not entitled to transfer the source code in any form to third parties without prior written consent of Würth Elektronik eiSos.

You are not allowed to reproduce, translate, reverse engineer, decompile, disassemble or create derivative works of the incorporated Software and the source code in whole or in part. No more extensive rights to use and exploit the products are granted to you.

6.2 Usage and obligations

The responsibility for the applicability and use of the Würth Elektronik eiSos wireless connectivity product with the incorporated Firmware in a particular customer design is always solely within the authority of the customer. Due to this fact, it is up to you to evaluate and investigate, where appropriate, and to decide whether the device with the specific product characteristics described in the product specification is valid and suitable for your respective application or not.

You are responsible for using the Würth Elektronik eiSos wireless connectivity product with the incorporated Firmware in compliance with all applicable product liability and product safety laws. You acknowledge to minimize the risk of loss and harm to individuals and bear the risk for failure leading to personal injury or death due to your usage of the product.

Würth Elektronik eiSos' products with the incorporated Firmware are not authorized for use in safety-critical applications, or where a failure of the product is reasonably expected to cause severe personal injury or death. Moreover, Würth Elektronik eiSos' products with the incorporated Firmware are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. You shall inform Würth Elektronik eiSos about the intent of such usage before

design-in stage. In certain customer applications requiring a very high level of safety and in which the malfunction or failure of an electronic component could endanger human life or health, you must ensure to have all necessary expertise in the safety and regulatory ramifications of your applications. You acknowledge and agree that you are solely responsible for all legal, regulatory and safety-related requirements concerning your products and any use of Würth Elektronik eiSos' products with the incorporated Firmware in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by Würth Elektronik eiSos. YOU SHALL INDEMNIFY WÜRTH ELEKTRONIK EISOS AGAINST ANY DAMAGES ARISING OUT OF THE USE OF WÜRTH ELEKTRONIK EISOS' PRODUCTS WITH THE INCORPORATED FIRMWARE IN SUCH SAFETY-CRITICAL APPLICATIONS.

6.3 Ownership

The incorporated Firmware created by Würth Elektronik eiSos is and will remain the exclusive property of Würth Elektronik eiSos.

6.4 Firmware update(s)

You have the opportunity to request the current and actual Firmware for a bought wireless connectivity Product within the time of warranty. However, Würth Elektronik eiSos has no obligation to update a modules firmware in their production facilities, but can offer this as a service on request. The upload of firmware updates falls within your responsibility, e.g. via ACC or another software for firmware updates. Firmware updates will not be communicated automatically. It is within your responsibility to check the current version of a firmware in the latest version of the product manual on our website. The revision table in the product manual provides all necessary information about firmware updates. There is no right to be provided with binary files, so called "Firmware images", those could be flashed through JTAG, SWD, Spi-Bi-Wire, SPI or similar interfaces.

6.5 Disclaimer of warranty

THE FIRMWARE IS PROVIDED "AS IS". YOU ACKNOWLEDGE THAT WÜRTH ELEKTRONIK EISOS MAKES NO REPRESENTATIONS AND WARRANTIES OF ANY KIND RELATED TO, BUT NOT LIMITED TO THE NON-INFRINGEMENT OF THIRD PARTIES' INTELLECTUAL PROPERTY RIGHTS OR THE MERCHANTABILITY OR FITNESS FOR YOUR INTENDED PURPOSE OR USAGE. WÜRTH ELEKTRONIK EISOS DOES NOT WARRANT OR REPRESENT THAT ANY LICENSE, EITHER EXPRESS OR IMPLIED, IS GRANTED UNDER ANY PATENT RIGHT, COPYRIGHT, MASK WORK RIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT RELATING TO ANY COMBINATION, MACHINE, OR PROCESS IN WHICH THE WÜRTH ELEKTRONIK EISOS' PRODUCT WITH THE INCORPORATED FIRMWARE IS USED. INFORMATION PUBLISHED BY WÜRTH ELEKTRONIK EISOS REGARDING THIRD-PARTY PRODUCTS OR SERVICES DOES NOT CONSTITUTE A LICENSE FROM WÜRTH ELEKTRONIK EISOS TO USE SUCH PRODUCTS OR SERVICES OR A WARRANTY OR ENDORSEMENT THEREOF.

6.6 Limitation of liability

Any liability not expressly provided by Würth Elektronik eiSos shall be disclaimed. You agree to hold us harmless from any third-party claims related to your usage of the Würth Elektronik eiSos' products with the incorporated Firmware, software and source code. Würth Elektronik eiSos disclaims any liability for any alteration, development created by you or your customers as well as for any combination with other products.

6.7 Applicable law and jurisdiction

Applicable law to this license terms shall be the laws of the Federal Republic of Germany. Any dispute, claim or controversy arising out of or relating to this license terms shall be resolved and finally settled by the court competent for the location of Würth Elektronik eiSos' registered office.

6.8 Severability clause

If a provision of this license terms is or becomes invalid, unenforceable or null and void, this shall not affect the remaining provisions of the terms. The parties shall replace any such provisions with new valid provisions that most closely approximate the purpose of the terms.

6.9 Miscellaneous

Würth Elektronik eiSos reserves the right at any time to change this terms at its own discretion. It is your responsibility to check at Würth Elektronik eiSos homepage for any updates. Your continued usage of the products will be deemed as the acceptance of the change. We recommend you to be updated about the status of new firmware and software, which is available on our website or in our data sheet and manual, and to implement new software in your device where appropriate. By ordering a wireless connectivity product, you accept this license terms in all terms.

List of Figures

1	Configure the local GPIOs via remote device host	6
2	Read the configuration of the local GPIOs via remote device host	6
3	Configure the local GPIOs via local host	7
4	Read the configuration of the local GPIOs via local host	8
5	Set the output value of a GPIO via remote device	9
6	Read the input value of a GPIO via remote device	9
7	Set the output value of a GPIO via host controller	10
8	Read the input value of a GPIO via host controller	10
9	The terminal program hterm	11
10	The Würth Elektronik eiSos's tool Smart Commander	12
11	The terminal program hterm	16

List of Tables

1	Supported GPIO_IDs	4
---	------------------------------	---



more than you expect



**Internet
of Things**



**Monitoring
& Control**



**Automated Meter
Reading**

Contact:

Würth Elektronik eiSos GmbH & Co. KG
Division Wireless Connectivity & Sensors

Max-Eyth-Straße 1
74638 Waldenburg
Germany

Tel.: +49 651 99355-0
Fax.: +49 651 99355-69
www.we-online.com/wireless-connectivity

