

OPERATING INSTRUCTIONS:

① Pull the actuator upwards in the open position

② Insert the FFC cable vertically until the conductor almost disappears

③ Press actuator in the middle to make there is no gap and the actuator is locked

④ Press both ends of the actuator

PRECAUTIONS:

Ⓐ Pull the actuator as horizontally as possible by a proper force

Ⓑ Do not pull the actuator too far otherwise the stop limit (hook on actuator) may be broken

Ⓒ Do not keep FFC inclined when insertion

Ⓓ Don't keep conductor toward actuator

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com		CREATED AK	CHECKED GM		
		DESCRIPTION Precaution FFC			
		REVISION 001.000	STATUS Valid	DATE (YYYY-MM-DD) 2018-05-16	BUSINESS UNIT eiCan

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.