

Image: Description of the state of the								Finher	103.					
Image: market with the set of the s								Propertie	s			Value	Unit	
$\frac{ \mathbf{x} ^2}{ \mathbf{x} ^2} + \frac{ \mathbf{x} ^2}{ \mathbf{x} ^2} + $								Material			(Cu-EPT, EN13600		
Image: Properties: I								Surface						
Image: Source of the source								Screw			M10			
Image:		-(+-)- □ ≥					Wire Cro	ss Section			95	mm ²	
L1 L3 Image: Contorm or declared (EC) 1907/2008] Image: Free Contorm (EC 0/249-2:21) Image: Free Contorn (EC 0/249-2:21) Image: Free Contorn (EC 0/249-2:21) Image: Free Solution (In original contorn)								Certifi	Certification:					
Image: rest in the second second part of the second second part								RoHS Ap	proval		Compliant	[2011/65/EU&2015;	/863]	
Image: Pree Contorn (JEDEC JS7089) Image: Pree Sol Cup to +125 °C Image: Pree Image: Pree Image:	 L1 		<u>L3</u>					REACh A	pproval		Conform or	declared [(EC)1907/	2006]	
$\overbrace{\begin{tindependence}{c} \\ \hline \\ $								Halogen	Free		Confc	rm [IEC 61249-2-21]	
$\frac{1}{2}$								Halogen	Free		Conf	orm [JEDEC JS709B]	1	
Properties Value Unit Length L1 48 mm Length L2 24 mm Length L3 12 mm Width W 26 mm Diameter Ø D 10.5 mm Inner Diameter Ø D 13.5 mm Wigth W Wigth Wigth Wigth Wigth Wigth Wigth Wigth Busiest Mit Wigth Wigth Busiest Mit Status Wigth Wigth Busiest Mit Status Migne Migne<	 ■∎							Operatin Storage packagin	g Temperature Conditions (in (1g)	original		40 °C ;<75 % rH		
Length L2 24 mm Length L2 24 mm Length L3 12 mm Width W 26 mm Diameter Ø D 10.5 mm Inner Diameter Ø ID 13.5 mm Weithelener U 4.2 mm Using data 4.2 10.5 mm Inner Diameter Ø ID 13.5 mm Würth Elektronik elsos GmbH & Co. K6 EMC & Inductive Solutions Maz-Byth-Str. 1 Würth Elektronik elsos GmbH & Co. K6 EMC & Inductive Solutions War-CLUG Tubular Cable Lugs ORDER CODE Busness unt	-		Value	Unit						-1				
Length L2 24 mm Length L3 12 mm Width W 26 mm Diameter Ø D 10.5 mm Inner Diameter Ø ID 13.5 mm Weith W Q26 Würth Elektronik elsos GribH & Co. KG Wirth Elektronik elsos GribH & So. Stratus Weith Elektronik elsos GribH & So. KG Wirth Elektronik elsos GribH & So. Stratus Wirth Elektronik elsos GribH & So. KG Wirth Elektronik elsos GribH & So. Stratus Wirth Elektronik elsos GribH & So. KG Wirth Elektronik elsos GribH & So. Stratus Wirth Elektronik elsos GribH & So. KG Wirth Elektronik elsos GribH & So. Stratus Weith Elektronik elsos GribH & So. KG Wirth Elektronik elsos GribH & So. Stratus Wirth Elektronik elsos GribH & So. KG Wirth Elektronik elsos GribH & So. Stratus Wirth Elektronik elsos GribH & So. Stratus Wa-CLUG Tubular Cable Lugs Wastess wirt Stratus Stratus Page Wirth Elektronik elsos GribH & So. Stratus More THAN Wirth Elektronik elsos GribH & So. Stratus Machematica Wirth Elektronik elsos GribH & So. Stratus More THAN Wirth Elektronik elsos GribH & So. Stratus Machematica Wirth Elektronik elsos GribH & So. Stratus Wirth Elektronik elsos GribH & So. Stratus Machematica Machemat		L ₁	48	mm	Ra							PROJECTION METHOD	- []	
Length L ₃ 12 mm Width W 26 mm Diameter Ø D 10.5 mm Inner Diameter Ø ID 13.5 mm Weight 42 mm Using Langth Langth With Elektronik elSos GmbH & Co. KG With Elektronik elSos GmbH & Co. KG Max-Eght > Status With Elektronik elSos GmbH & Co. KG Max-Eght > Status With Elektronik elSos GmbH & Co. KG Max-Eght > Status With Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Max-Eght > Status Wurdt Elektronik elSos GmbH & Co. KG Wu	Length	L ₂	24	mm										
Width W 26 mm Diameter Ø D 10.5 mm Inner Diameter Ø ID 13.5 mm Weighted U 4.2 mm	Length	L ₃	12	mm	COMPLIANT COMPLIANT	FREE				oular Cable	e Luas			
Diameter Ø D 10.5 mm Würth Elektronik NGRE THAN Mak-Eth-Su-1 Status 5581095 Inner Diameter Ø ID 13.5 mm V/F More THAN OU EXPECT More THAN Www.wo-online.com Figure 40(07) 42 945 - 0 Www.wo-online.com Busness unit status Proc	Width	W	26	mm			Würth Elektronik eiSos GmbH & Co. KG					ORDER CODE		
Inner Diameter Ø ID 13.5 mm I// T MORE THAN Tel: +49 (0) 79 42 945 - 0 Business unit status PAGE	Diameter	ØD	10.5	mm	N N		Max-Eyth-Str. 1							
Height H 4.3 mm YOU EXPECT www.we-online.com eiSos@we-online.com	Inner Diameter	ØID	13.5	mm		ORE THAN	Germany Tel. +49 (0) 79 42 945 - 0	-			BUSINESS UNIT		PAGE	
	Height	Н	4.3	mm	Y Y	DU EXPECT	www.we-online.com				eiCan	Valid	1 1	

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation, transportation, transportation, medical, public information network etc.. Würth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Properties:

Further information

Component Libraries:

Ð	<u>3D_5581095</u>
100	Download_IGS_5581095
P	Download STD 5591005

Download_STP_5581095

Free Sample Order:

Order free samples of this article directly here!

				REVISION 002.001	DATE (YYYY-MM-DD) 2024-11-29	general tolerance DIN 46235	-	PROJECTION METHOD	 ⊕-
ROHS REACH HALOGEN COMPLIANT COMPLIANT FREE			DESCRIPTION	.UG Tub	ular Cable	Lugs			
		Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany					ORDER CODE	1095	
MORE TH YOU EXPE		elementary Tell. +49 (0) 79 42 945 - 0 www.we-online.com elSos@we-online.com				BUSINESS UNIT eiCan	status Valid		PAGE 2/4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be information unter a fuller of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use, availation, nucleac exact for unter a higher safety standard and reliability standard is especially required by severe teels and interview of the standard for use in areas such as military, aerospace, availation, transportation signal, disaster prevention, medical, public information network etc... Würth Elektronik elSos GmbH & Co KG must be informed about the intern of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electronic advicual truth and truth and truth standard and require high stated and and require high stated and

Cautions and Warnings:

The following conditions apply to all goods within the product series of WA-CLUG of Würth Elektronik eiSos GmbH & Co. KG:

General:

- This mechanical component is designed and manufactured for use in general electronic equipment.
- Würth Elektronik must be asked for written approval (following the PPAP procedure) before incorporating the components into any
 equipment in fields such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control,
 ship control), transportation signal, disaster prevention, medical, public information network, etc. where higher safety and reliability are
 especially required and/or if there is the possibility of direct damage or human injury.
- Mechanical components that will be used in safety-critical or high-reliability applications, should be pre-evaluated by the customer.
- The component is designed and manufactured to be used within the datasheet specified values. If the usage and operation conditions
 specified in the datasheet are not met, the component may be damaged or dissolved.
- Do not drop or impact the components, the component may be damaged.
- Würth Elektronik products are qualified according to international standards, which are listed in each product reliability report. Würth
 Elektronik does not warrant any customer qualified product characteristics beyond Würth Elektroniks' specifications, for its validity and
 sustainability over time.
- The responsibility for the function of the application of the customer specific products and use in a particular customer design is always
 the full and autonomous responsibility of the customer. All technical specification for standard products also apply to customer specific
 products.

Product Specific:

Cleaning and Washing:

- Washing agents used during the production to clean the customer application might damage or change the characteristics of the components. Washing agents may have a negative effect on the long-term functionality of the product.
- Using a brush during the cleaning process may damage the component. Therefore, we do not recommend using a brush during the PCB cleaning process.

Potting and Coating:

• If the product is potted in the customer application, the potting material might shrink or expand during and after hardening. Shrinking could lead to an incomplete seal, allowing contaminants into the components. Expansion could damage the components. We recommend a manual inspection after potting or coating to avoid these effects.

Storage Conditions:

- A storage of Würth Elektronik products for longer than 12 months is not recommended. Within other effects, the terminals may suffer degradation, resulting in bad processability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- Do not expose the components to direct sunlight.
- The storage conditions in the original packaging are defined according to DIN EN 61760-2.
- The storage conditions stated in the original packaging apply to the storage time and not to the transportation time of the components.

Packaging:

• The packaging specifications apply only to purchase orders comprising whole packaging units. If the ordered quantity exceeds or is lower than the specified packaging unit, packaging in accordance with the packaging specifications cannot be ensured.

Handling:

- · The maximum permissible torques must be complied with to prevent mechanical destruction of the component and PCB
- If a component is pre-assembled with an adhesive tape, the adhesive duration cannot be guaranteed. This depends on the surface
 where the component will be mounted on. It also depends on the environmental conditions the component is exposed to. The customer
 has to evaluate this for his specific application.
- Violation of the technical product specifications will void the warranty.
- Coated metal parts may have spots and/or deposits because of the rinsing and drying process during plating. The storage and
 processability are not affected.
- The temperature rise of the component must be taken into consideration. The operating temperature is comprised of ambient temperature and temperature rise of the component. The operating temperature of the component shall not exceed the maximum temperature specified.

These cautions and warnings comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable. However, no responsibility is assumed for inaccuracies or incompleteness.

				CHECKED KGa	REVISION 002.001	DATE (YYYY-MM-DD) 2024-11-29	general tolerance DIN 46235	_	PROJECTION METHOD	$- \bigcirc ($	€-
	ROHS REACH COMPLIANT COMPLIANT	HALOGEN FREE		DESCRIPTION	.UG Tub	ular Cable	Lugs				
	L-//5	WURTH ELEKTRONIK	Wirth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Gerrmany					ORDER CODI	1095		
		MORE THAN YOU EXPECT	elinariy Tel. +49 (0) 79 42 945 - 0 www.we-online.com elSos@we-online.com				BUSINESS UNIT eiCan	status Valid		1	PAGE 3/4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be informed about the intern of such usage before the design-in stage. In addition, sufficient reliability evaluation, transportation, signal, disaster prevention, medical, public information network etc... Würth Elektronik elSos GmbH & Co KG must be informed about the intern of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electricia circuits that and reliability functions or performance.

Important Notes

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

	CHECKED KGa	REVISION 002.001	DATE (YYYY-MM-DD) 2024-11-29	general tolerance DIN 46235		PROJECTION METHOD	$\exists $	⊕-	
			WA-CLUG Tubular Cable Lugs						
	RONIK 74638 Waldenburg				_	ORDER CODE	1095		
MORE THAN YOU EXPECT	Tel. +44 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com				BUSINESS UNIT eiCan	status Valid		- 1	PAGE 4/4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electronic circuits that require high asteging and reliability functions or performance.