	1		2		3	4	5		T
	2	After cabling	2,54		Before cabling	TECHNICAL CHARA MATERIAL INSULATOR: PBT FLAMMABILITY RAT COLOR: BLACK METAL: PHOSPHOF PLATING: TIN QUALITY CLASS: 25 ENVIRONMENTAL OPERATING TEMPE COMPLIANCE: LEAI ELECTRICAL CURRENT RATING: WORKING VOLTAG	CTERISTICS TING: UL94V0 R BRONZE S MATING CYCLES ERATURE: -40°C UP TO +125°C D FREE AND ROHS 3 A E: 50 VAC ULTAGE: 500 VAC/MIN TANCE: >1000 MΩ NCE: 20 mΩ MAX		E
G F E D	0HS Compliant	DESCRIPTION	AK		A = (nb. pin B = (nb. pin GENERAL TOLERANCE ±0,1	x pitch)			-
C B A	07-DEC-15 20-OCT-15 19-SEP-14	MECHANICAL / PACK UPDATE PDF	AK AF	PPROVAL: BBu	UNIT: MM SCALE: SHEET: 1/2	DESCRIPTION: 2.54 MM AUTOCOM SING IDC RECEPTACLE FOR AWG#24-22 WITH SIDE WERI PART NO: 661 0xx 152 122		SIZE	
REV	DATE	FILE	BY		DRAW: AK				

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONIK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	Ъ
В					SCALE:			Γ
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			