	1			2	3	4	5		\Box
	oHS Compliant	26.0	<u>2.6</u>	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	2.60 ntacts	TECHNICAL CHARACTE MATERIAL INSULATOR: PA 66 FLAMABILITY RATING: L COLOR: GREEN METAL HOUSING: BRAS	RISTICS JL94-V0 IS (CuZn) IEL ZINC PLATING "-" SLOT TY PLATED URE: -40 UP TO 105°C EE AND ROHS CULus VDE 15A 17A 300VAC 300VA GE: 1.6KV 2.5KV : 20 mOhm MAX 114 402 24-12 AWG / 0.205-3.3' 3.5 Lb.In - 0.4 Nm	C MM ²	
G				PROJECTION:	GENERAL TOLERANCE				
F E					.X = ⁺ /_ 0.2				╞
E D				\neg	.XX = ⁺ /_ 0.15				
C D					UNIT: MM	DESCRIPTION: SERIE 3445 - 5.08MM HORIZON		SIZE	_
B	24-JUL-14	DRAWINGS	AS	APPROVAL: RJ	SCALE:	WITH HOOK ON BACK SIDE - WR-TBL	TAL GADLE ENTRY PLUG	SIZE	
	04-NOV-08	PDF	JP		SHEET: 1/2	WERI PART NO: 691 344 510 0xx		- A4	L
A			JE	1	UNLLI. 1/2	TTELLI FALLING. 031 344 310 0AA			

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	oHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE]
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĬK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	lD
В]	SCALE:			٢
A	10-SEP-14	PDF	QL	1	SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			