







Dimensions: [mm]




Unless otherwise defined tolerance: $\pm 0.25\text{mm}$

Recommended Hole Pattern: [mm] (Top View)



Unless otherwise defined tolerance: $\pm 0.10\text{mm}$

Recommended Panel Cutout: [mm]



Unless otherwise defined tolerance: $\pm 0,10\text{mm}$

Product Marking:


| | |
|-----------|-------------|
| PN-Code | 7499031120A |
| Date-Code | YYWW |



Würth Elektronik eiSos GmbH & Co. KG
EMC & Inductive Solutions
Max-Eyth-Str. 1
74638 Waldenburg
Germany
Tel. +49 (0) 79 42 945 - 0
www.we-online.com
eiSos@we-online.com

| | | | | |
|------------------------------------|------------------------|---------------------------------|--------------------------------------|-----------------------|
| CHECKED FeE | REVISION 002.001 | DATE (YYYY-MM-DD) 2108-12-31 | GENERAL TOLERANCE DIN ISO 2768-1m | PROJECTION METHOD |
| DESCRIPTION WE-RJ45LAN | | | ORDER CODE 7499031120A | |
| SIZE/TYPE 100BT, 1x4, down, ETR | BUSINESS UNIT eiSos | STATUS Draft | PAGE 1/9 | |

Schematic:



| | | | | | |
|---|---|---------------------|---------------------------------|--------------------------------------|----------------------------------|
| | CHECKED FeE | REVISION 002.001 | DATE (YYYY-MM-DD) 2108-12-31 | GENERAL TOLERANCE DIN ISO 2768-1m | PROJECTION METHOD |
| | DESCRIPTION WE-RJ45LAN | | | | ORDER CODE 7499031120A |
| WÜRTH ELEKTRONIK MORE THAN YOU EXPECT | Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com | | | BUSINESS UNIT eiSos | PAGE 2/9 |
| | SIZE/TYPE 100BT, 1x4, down, ETR | STATUS Draft | | | |

Electrical Properties:

| Properties | | Test conditions | Value | Unit | Tol. |
|-----------------------------|----------------|-------------------------|-------|--------|------|
| Inductance | L | 100 kHz / 100 mV @ 8 mA | 350 | µH | min. |
| Insulation Test Voltage | V _T | 1 min | 2250 | V (DC) | min. |
| Insertion Loss | IL | 1-100 MHz | -1 | dB | max. |
| Return Loss | RL | 1-30 MHz @ 100 Ω | -16 | dB | min. |
| Return Loss | RL | 30-60 MHz @ 100 Ω | -12 | dB | min. |
| Return Loss | RL | 60-80 MHz @ 100 Ω | -10 | dB | min. |
| Return Loss | RL | 80-100 MHz @ 100 Ω | -10 | dB | min. |
| Crosstalk | CT | 1-60 MHz | -30 | dB | min. |
| Crosstalk | CT | 60-100 MHz | -30 | dB | min. |
| Common Mode Rejection Ratio | CMRR | 1-50 MHz | -30 | dB | min. |
| Common Mode Rejection Ratio | CMRR | 30-60 MHz | -20 | dB | min. |
| Common Mode Rejection Ratio | CMRR | 60-100 MHz | -20 | dB | min. |
| Turns Ratio | n | | 1 : 1 | | ±2% |
| Data rate | 100BASE-TX | | | | |

LED Electrical & Optical Properties:

| Properties | | Test conditions | Value | | Unit |
|------------------|----------------|-----------------|-------|------|------|
| | | | min. | max. | |
| Forward Voltage | V _F | 20 mA | 1.8 | 2.4 | V |
| LED (Left-Right) | yellow-green | | | | |

General Information:

| Properties | Value | Unit | Tol. |
|--|------------------------|--------|------|
| Operating Temperature | -40 °C up to +85 °C | | |
| Storage Conditions (in original packaging) | up to 40 °C; < 75 % rH | | |
| Moisture Sensitivity Level (MSL) | 1 | | |
| Mating Cycle | 750 | Cycles | min. |

General Information:






| Properties | Value | Unit | Tol. |
|--|-------|------|------|
| Compliant with IEEE 802.3u | | | |
| Test conditions of Electrical Properties: +20 °C, 33 % rH if not specified differently | | | |



Certification:

| | |
|----------------|-------------------------------------|
| RoHS Approval | Compliant [2011/65/EU&2015/863] |
| REACH Approval | Conform or declared [(EC)1907/2006] |
| cURus Approval | E472316 [UL 62368-1] |

Material Properties:

| | |
|-------------------------------------|----------------------------|
| Plastic Housing Material | Thermoplastic PA66 Black |
| Plastic Housing Flammability Rating | UL94 V-0 |
| Shielding Material | Brass |
| Shielding Plating | 50µ" Nickel |
| Contact Material | Phosphor Bronze |
| Contact Plating | 30µ" Gold over 50µ" Nickel |

| | | | | | |
|--|---|------------------------|---------------------------------|--------------------------------------|--|
|    | CHECKED FeE | REVISION 002.001 | DATE (YYYY-MM-DD) 2108-12-31 | GENERAL TOLERANCE DIN ISO 2768-1m | PROJECTION METHOD  |
| | DESCRIPTION WE-RJ45LAN | | | | |
|  WURTH ELEKTRONIK MORE THAN YOU EXPECT | Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com | | | ORDER CODE 7499031120A | |
| | SIZE/TYPE 100BT, 1x4, down, ETR | BUSINESS UNIT eiSos | STATUS Draft | PAGE 3/9 | |




| | L (mm) | W (mm) | H (mm) | No. of Locking Device (pcs.) | Qty. (pcs.) | Material |
|-----------|--------|--------|--------|------------------------------|-------------|----------|
| Tolerance | typ. | typ. | typ. | | | |
| Value | 530.00 | 23.40 | 23.70 | 2 | 8 | PVC |



Würth Elektronik eiSos GmbH & Co. KG
 EMC & Inductive Solutions
 Max-Eyth-Str. 1
 74638 Waldenburger
 Germany
 Tel. +49 (0) 79 42 945 - 0
 www.we-online.com
 eiSos@we-online.com

| | | | | |
|------------------------------------|---------------------|---------------------------------|--------------------------------------|-----------------------|
| CHECKED FeE | REVISION 002.001 | DATE (YYYY-MM-DD) 2108-12-31 | GENERAL TOLERANCE DIN ISO 2768-1m | PROJECTION METHOD |
| DESCRIPTION WE-RJ45LAN | | | ORDER CODE 7499031120A | |
| SIZE/TYPE 100BT, 1x4, down, ETR | | BUSINESS UNIT eiSos | STATUS Draft | PAGE 4/9 |



| | L _c (mm) | W _c (mm) | H _c (mm) | No. of Tube (pcs.) | Qty. (pcs.) | Material |
|-----------|------------------------|------------------------|------------------------|-----------------------|----------------|----------|
| Tolerance | typ. | typ. | typ. | | | |
| Value | 550.00 | 265.00 | 165.00 | 60 | 480 | Paper |



Würth Elektronik eiSos GmbH & Co. KG
 EMC & Inductive Solutions
 Max-Eyth-Str. 1
 74638 Waldenburg
 Germany
 Tel. +49 (0) 79 42 945 - 0
 www.we-online.com
 eiSos@we-online.com

| | | | | |
|------------------------------------|---------------------|---------------------------------|--------------------------------------|--------------------------|
| CHECKED FeE | REVISION 002.001 | DATE (YYYY-MM-DD) 2108-12-31 | GENERAL TOLERANCE DIN ISO 2768-1m | PROJECTION METHOD |
| DESCRIPTION WE-RJ45LAN | | | ORDER CODE 7499031120A | |
| SIZE/TYPE 100BT, 1x4, down, ETR | | BUSINESS UNIT eiSos | STATUS Draft | PAGE 5/9 |






Classification Wave Soldering Profile:



Classification Wave Soldering Profile:

| Profile Feature | | Pb-Free Assembly | Sn-Pb Assembly |
|---|-------------------------|---|---|
| Preheat Temperature Min | $T_{s \min}$ | 100 °C | 100 °C |
| Preheat Temperature Typical | $T_{s \text{ typical}}$ | 120 °C | 120 °C |
| Preheat Temperature Max | $T_{s \max}$ | 130 °C | 130 °C |
| Preheat Time t_s from $T_{s \min}$ to $T_{s \max}$ | t_s | 70 seconds | 70 seconds |
| Ramp-up Rate Δ Temperature from $T_{s \text{ typical}}$ to T_p | ΔT | 150 °C max. | 150 °C max. |
| Peak Temperature | T_p | 250 °C - 260 °C | 235 °C - 260 °C |
| Time of actual peak temperature | t_p | max. 10 seconds max. 5 seconds each wave | max. 10 seconds max. 5 seconds each wave |
| Ramp-down Rate, Min | | ~ 2 K/ second | ~ 2 K/ second |
| Ramp-down Rate, Typical | | ~ 3.5 K/ second | ~ 3.5 K/ second |
| Ramp-down Rate, Max | | ~ 5 K/ second | ~ 5 K/ second |
| Time 25 °C to 25 °C | | 4 minutes | 4 minutes |

refer to EN61760-1:2006

| | | | | | | |
|--|---|---------------------|---------------------------------|--------------------------------------|--|-------------|
|    | CHECKED FeE | REVISION 002.001 | DATE (YYYY-MM-DD) 2108-12-31 | GENERAL TOLERANCE DIN ISO 2768-1m | PROJECTION METHOD  | |
| | DESCRIPTION WE-RJ45LAN | | | | ORDER CODE 7499031120A | |
|  WÜRTH ELEKTRONIK MORE THAN YOU EXPECT | Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com | | | BUSINESS UNIT eiSos | STATUS Draft | PAGE 6/9 |
| | SIZE/TYPE 100BT, 1x4, down, ETR | | | | | |

Further information

Component Libraries:






| | |
|-------------|---|
| 3D | Download_3D_WE-LAN-RJ45_7499031120A |
| Altium | Altium_WE-RJ45 LAN (25d) |
| Cadence17-2 | Downloads_CADENCE_WE-RJ45_LAN (25e) |
| Cadstar | Cadstar_WE-RJ45 LAN (21c) |
| Eagle | Eagle_WE-RJ45-LAN (25e) |
| IGS | Download_IGS_7499031120A |
| KiCad | KiCad_WE-RJ45LAN (25b) |
| STP | Download_STP_7499031120A |

Free Sample Order:

[Order free samples of this article directly here!](#)

REDEXPERT:

[Calculate losses for 7499031120A in REDEXPERT](#)

| | | | | | | | | |
|---|---|--|-----------------------|---------------|-------------------|-------------------|--------------------|---|
|  RoHS COMPLIANT |  REACH COMPLIANT |  | CHECKED | REVISION | DATE (YYYY-MM-DD) | GENERAL TOLERANCE | PROJECTION METHOD |  |
| | | | FeE | 002.001 | 2108-12-31 | DIN ISO 2768-1m | | |
|  WÜRTH ELEKTRONIK MORE THAN YOU EXPECT | | | DESCRIPTION | | | | ORDER CODE | |
| | | | WE-RJ45LAN | | | | 7499031120A | |
| <p>Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com</p> | | | SIZE/TYPE | BUSINESS UNIT | STATUS | PAGE | | |
| | | | 100BT, 1x4, down, ETR | eiSos | Draft | 7/9 | | |

Cautions and Warnings:

The following conditions apply to all goods within the product series of **WE-RJ45LAN** of Würth Elektronik eiSos GmbH & Co. KG:

General:

- This electronic component was designed and manufactured for use in general electronic equipment.
- Würth Elektronik must be asked for written approval (following the PPAP procedure) before incorporating the components into any equipment in fields such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required and/or if there is the possibility of direct damage or human injury.
- Electronic components that will be used in safety-critical or high-reliability applications, should be pre-evaluated by the customer.
- The component is designed and manufactured to be used within the datasheet specified values. If the usage and operation conditions specified in the datasheet are not met, the wire insulation may be damaged or dissolved.
- Do not drop or impact the components, the component may be damaged.
- Würth Elektronik products are qualified according to international standards, which are listed in each product reliability report. Würth Elektronik does not warrant any customer qualified product characteristics beyond Würth Elektronik's specifications, for its validity and sustainability over time.
- The customer is responsible for the functionality of their own products. All technical specifications for standard products also apply to customer specific products.

Product specific:

Soldering:

- The solder profile must comply with the technical product specifications. All other profiles will void the warranty.
- All other soldering methods are at the customers' own risk.
- Strong forces which may affect the coplanarity of the components' electrical connection with the PCB (i.e. pins), can damage the part, resulting in a void of the warranty.

Cleaning and Washing:

- Washing agents used during the production to clean the customer application may damage or change the characteristics of the wire insulation, marking or plating. Washing agents may have a negative effect on the long-term functionality of the product.
- Using a brush during the cleaning process could break the wire due to its small diameter. Therefore, we do not recommend using a brush during the PCB cleaning process.

Potting:

- If the product is potted in the customer application, the potting material may shrink or expand during and after hardening. Shrinking could lead to an incomplete seal, allowing contaminants into the core. Expansion could damage the components. We recommend a manual inspection after potting to avoid these effects.

Storage Conditions:

- A storage of Würth Elektronik products for longer than 12 months is not recommended. Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- Do not expose the components to direct sunlight.
- The storage conditions in the original packaging are defined according to DIN EN 61760-2.
- The storage conditions stated in the original packaging apply to the storage time and not to the transportation time of the components.




Packaging

- The packaging specifications apply only to purchase orders comprising whole packaging units. If the ordered quantity exceeds or is lower than the specified packaging unit, packaging in accordance with the packaging specifications cannot be ensured.

Handling:

- Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty.
- Applying currents with audio-frequency signals may result in audible noise due to the magnetostrictive material properties.
- The temperature rise of the component must be taken into consideration. The operating temperature is comprised of ambient temperature and temperature rise of the component. The operating temperature of the component shall not exceed the maximum temperature specified.

These cautions and warnings comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable. However, no responsibility is assumed for inaccuracies or incompleteness.

| | | | | | |
|---|---|---------------------|---------------------------------|--------------------------------------|--|
|  | CHECKED FeE | REVISION 002.001 | DATE (YYYY-MM-DD) 2108-12-31 | GENERAL TOLERANCE DIN ISO 2768-1m | PROJECTION METHOD  |
| | DESCRIPTION WE-RJ45LAN | | | | ORDER CODE 7499031120A |
|  WÜRTH ELEKTRONIK MORE THAN YOU EXPECT | Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com | | | BUSINESS UNIT eiSos | PAGE 8/9 |
| | SIZE/TYPE 100BT, 1x4, down, ETR | STATUS Draft | | | |

Important Notes

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

6. Product Life Cycle






Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG. Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

| | | | | | | |
|---|--|----------------|------------------------|---------------------------------|--------------------------------------|--|
|    | | CHECKED FeE | REVISION 002.001 | DATE (YYYY-MM-DD) 2108-12-31 | GENERAL TOLERANCE DIN ISO 2768-1m | PROJECTION METHOD  |
|  WÜRTH ELEKTRONIK MORE THAN YOU EXPECT | | | | | DESCRIPTION WE-RJ45LAN | |
| Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com | | | | | ORDER CODE 7499031120A | |
| SIZE/TYPE 100BT, 1x4, down, ETR | | | BUSINESS UNIT eiSos | STATUS Draft | PAGE 9/9 | |