



Dimensions: [mm]




Product Marking:

|         |                                |
|---------|--------------------------------|
| Pin 1   | •                              |
| Marking | 750319917<br>Lot and date code |

Recommended Land Pattern: [mm]



Schematic:



Electrical Properties:

| Properties               |                   | Test conditions                | Value       | Unit   | Tol. |
|--------------------------|-------------------|--------------------------------|-------------|--------|------|
| Inductance               | L                 | N1/ 100 kHz/ 100 mV            | 0.9         | mH     | min. |
| Turns Ratio              | n                 | N1 : N2 : N3                   | 1:1.71:1.71 |        |      |
| DC Resistance 1          | R <sub>DC 1</sub> | N1/ 20 °C                      | 0.375       | Ω      | max. |
| DC Resistance 2          | R <sub>DC 2</sub> | N2/ 20 °C                      | 0.61        | Ω      | max. |
| DC Resistance 3          | R <sub>DC 3</sub> | N3/ 20 °C                      | 0.61        | Ω      | max. |
| Leakage Inductance       | L <sub>S</sub>    | N1/ 100 kHz/ 100 mV            | 480         | nH     | max. |
| Voltage-µSecond          | ∫ Udt             | N1/ bipolar waveform           | 147         | Vµs    |      |
| Interwinding Capacitance | C <sub>WW</sub>   | N1 => N2,3/<br>100 kHz/ 100 mV | 8.8         | pF     | typ. |
| Interwinding Capacitance | C <sub>WW</sub>   | N1 => N2/<br>100 kHz/ 100 mV   | 7.1         | pF     | typ. |
| Interwinding Capacitance | C <sub>WW</sub>   | N1 => N3/<br>100 kHz/ 100 mV   | 7.1         | pF     | typ. |
| Insulation Test Voltage  | V <sub>T</sub>    | N1 => N2,3                     | 5500        | V (AC) |      |
| Insulation Test Voltage  | V <sub>T 2</sub>  | N2 => N3                       | 2000        | V (AC) |      |

General Information:

|                                                         |                             |
|---------------------------------------------------------|-----------------------------|
| Operating Temperature                                   | -40 °C up to +125 °C        |
| Storage Conditions (in original packaging)              | 5 °C up to 40 °C; < 75 % rH |
| Moisture Sensitivity Level (MSL)                        | 1                           |
| Electrical Specifications @ 25°C unless otherwise noted |                             |

Supply only with DC < 75 V and AC < 50 V; exceeding these limits invokes additional product-compliance requirements. Note: functionality above ≈15.5 VDC has not been verified.



WURTH  
ELEKTRONIK  
MORE THAN  
YOU EXPECT

Wurth Electronics Midcom Inc. Headquarters  
121 Airport Drive  
57201 Watertown, SD  
United States  
Phone: +1 (605) 886-4385  
www.we-online.com/midcom  
midcom@we-online.com

|                                                                    |                         |                                 |                                  |                                |
|--------------------------------------------------------------------|-------------------------|---------------------------------|----------------------------------|--------------------------------|
| CHECKED<br>EOI                                                     | REVISION<br>001.001     | DATE (YYYY-MM-DD)<br>2026-07-17 | GENERAL TOLERANCE<br>ISO 2768-1m | PROJECTION<br>METHOD<br>       |
| DESCRIPTION<br><b>WE-AGDT Auxiliary Gate Drive<br/>Transformer</b> |                         |                                 |                                  | ORDER CODE<br><b>750319917</b> |
| SIZE/TYPE<br>2015                                                  | BUSINESS UNIT<br>Midcom | STATUS<br>Valid                 | PAGE<br>1/8                      |                                |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos Group products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos Group must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Typical Application:

| Properties          |                     | Value | Unit |
|---------------------|---------------------|-------|------|
| Input Voltage       | V <sub>in</sub>     | 15.5  | V    |
| Switching Frequency | f <sub>switch</sub> | 100   | kHz  |
| Output Voltage 1    | V <sub>Out1</sub>   | 38    | V    |
| Output Current 1    | I <sub>Out1</sub>   | 60    | mA   |
| Output Voltage 2    | V <sub>Out2</sub>   | 38    | V    |
| Output Current 2    | I <sub>Out2</sub>   | 60    | mA   |

Input: N1  
Output 1: N2 Bipolar 25V -13V Total 38V  
Output 2: N3 Bipolar 25V -13V Total 38V  
Table shows an example full bridge application with a duty cycle of 14%.  
Before getting started read the Tutorials for WE-AGDT on page 6.

Designed to Comply With:

| Standard                                                      | Condition                                                                                                                                                                                                                                                                      |
|---------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IEC60664-1                                                    | 15.4mm of creepage and clearance between PRI and SEC.<br><br>5.75mm of creepage and clearance between SEC and SEC.                                                                                                                                                             |
| IEC62368-1, EN62368-1, UL62368-1/CSA62368-1 and AS/NZS62368.1 | Basic insulation for a primary circuit at a working voltage of 1000Vrms, 1400Vpeak, Overvoltage Category III, Pollution Degree 2.<br><br>Reinforced insulation for a primary circuit at a working voltage of 750Vrms, 1060Vpeak, Overvoltage Category III, Pollution Degree 2. |
| IEC61800-5-1 and EN61800-5-1                                  | Basic insulation for a primary circuit at a working voltage of 1000Vrms, 1400Vpeak, Overvoltage Category III, Pollution Degree 2.<br><br>Reinforced insulation for a primary circuit at a working voltage of 750Vrms, 1060Vpeak, Overvoltage Category III, Pollution Degree 2. |

Electrical Safety Standard Properties:

| Properties        | Test conditions                                                       | Value | Unit |
|-------------------|-----------------------------------------------------------------------|-------|------|
| Surge             | N1=> N2,3/ 1.2 x 50usec 5± repetitions                                | 12    | kV   |
| Partial Discharge | N1=> N2,3/ 1987Vpk Inception 5 seconds, 1590Vpk Extinction 15 seconds | <10   | pC   |

Certification:



|                         |                                     |
|-------------------------|-------------------------------------|
| RoHS Approval           | Compliant [2011/65/EU&2015/863]     |
| REACH Approval          | Conform or declared [(EC)1907/2006] |
| Halogen Free            | Conform [JEDEC JS709B]              |
| Component Qualification | AEC-Q200 Grade 1                    |

The data may change depending on the specific customer's application context (e.g. component interactions, environmental parameters, and their combined effects). The customer is solely responsible for deciding whether, how, and to what extent to evaluate, investigate, and test whether the product is suitable for their specific application, and bears full responsibility for that assessment.

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos Group products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos Group must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Packaging Specification - Tape: [mm]

Packaging Specification - Reel: [mm]




|           | Tape Type | A0<br>(mm) | B0<br>(mm) | W<br>(mm) | T<br>(mm) | T1<br>(mm) | T2<br>(mm) | K0<br>(mm) | P0<br>(mm) | P1<br>(mm) | P2<br>(mm) | D0<br>(mm) | D0 / 2<br>(mm) | D1<br>(mm) | d<br>(mm) | E<br>(mm) | S<br>(mm) | F<br>(mm) | Material    | Qty.<br>(pcs.) |
|-----------|-----------|------------|------------|-----------|-----------|------------|------------|------------|------------|------------|------------|------------|----------------|------------|-----------|-----------|-----------|-----------|-------------|----------------|
| Tolerance |           | typ.       | typ.       | ±0.3      | ±0.05     | ±0.0025    | typ.       | typ.       | ±0.10      | ±0.10      | ±0.10      | ±0.05      | typ.           | +0.25      | typ.      | ±0.10     | ±0.30     | typ.      |             |                |
| Value     |           | 15.4       | 20.9       | 44        | 0.5       | 0.051      | 10.551     | 10.5       | 4          | 24         | 2          | 1.55       | 0.775          | 1.5        | 1.85      | 1.75      | 40.4      | 20.2      | Polystyrene | 250            |

|           | A<br>(mm) | B<br>(mm) | C<br>(mm) | D<br>(mm) | N<br>(mm) | W1<br>(mm) | W2<br>(mm) | W3<br>(mm) | W3<br>(mm) | Material    |
|-----------|-----------|-----------|-----------|-----------|-----------|------------|------------|------------|------------|-------------|
| Tolerance | max       | min.      | min.      | min.      | typ.      | +2.0       | max        | min.       | max        |             |
| Value     | 330,00    | 1,50      | 12,80     | 20,20     | 101,60    | 44,40      | 50,40      | 43,90      | 47,40      | Polystyrene |


This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos Group products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos Group must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Packaging Specification - Inner Carton: [mm]



|           | L <sub>ic</sub><br>(mm) | W <sub>ic</sub><br>(mm) | H <sub>ic</sub><br>(mm) | No. of<br>Reel (pcs.) | Qty.<br>(pcs.) | Material |
|-----------|-------------------------|-------------------------|-------------------------|-----------------------|----------------|----------|
| Tolerance | typ.                    | typ.                    | typ.                    |                       |                |          |
| Value     | 361,95                  | 339,73                  | 73,03                   | 1                     | 250            | Paper    |

Packaging Specification - Carton: [mm]



|           | L <sub>c</sub><br>(mm) | W <sub>c</sub><br>(mm) | H <sub>c</sub><br>(mm) | No. of<br>Inner Carton (pcs.) | Qty.<br>(pcs.) | Material |
|-----------|------------------------|------------------------|------------------------|-------------------------------|----------------|----------|
| Tolerance | typ.                   | typ.                   | typ.                   |                               |                |          |
| Value     | 365,12                 | 342,90                 | 230,00                 | 3                             | 750            | Paper    |





WURTH  
ELEKTRONIK

MORE THAN  
YOU EXPECT

Wurth Electronics Midcom Inc. Headquarters  
121 Airport Drive  
57201 Watertown, SD  
United States  
Phone: +1 (605) 886-4385  
www.we-online.com/midcom  
midcom@we-online.com

CHECKED  
EOI

REVISION  
001.001

DATE (YYYY-MM-DD)  
2026-07-17

GENERAL TOLERANCE  
ISO 2768-1m

PROJECTION  
METHOD  


DESCRIPTION  
**WE-AGDT Auxiliary Gate Drive  
Transformer**

SIZE/TYPE  
2015

BUSINESS UNIT  
Midcom

STATUS  
Valid

PAGE  
4/8

ORDER CODE  
**750319917**

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos Group products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos Group must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Classification Reflow Profile for SMT components:



Classification Reflow Soldering Profile:

| Profile Feature                                      |              | Value                            |
|------------------------------------------------------|--------------|----------------------------------|
| Preheat Temperature Min                              | $T_{s\ min}$ | 150 °C                           |
| Preheat Temperature Max                              | $T_{s\ max}$ | 200 °C                           |
| Preheat Time $t_s$ from $T_{s\ min}$ to $T_{s\ max}$ | $t_s$        | 60 - 120 seconds                 |
| Ramp-up Rate ( $T_L$ to $T_p$ )                      |              | 3 °C/ second max.                |
| Liquidous Temperature                                | $T_L$        | 217 °C                           |
| Time $t_L$ maintained above $T_L$                    | $t_L$        | 60 - 150 seconds                 |
| Peak package body temperature                        | $T_p$        | $T_p \leq T_c$ , see Table below |
| Time within 5°C of actual peak temperature           | $t_p$        | 20 - 30 seconds                  |
| Ramp-down Rate ( $T_p$ to $T_L$ )                    |              | 6 °C/ second max.                |
| Time 25°C to peak temperature                        |              | 8 minutes max.                   |

refer to IPC/ JEDEC J-STD-020E

Package Classification Reflow Temperature ( $T_c$ ):

| Properties                                           | Volume mm <sup>3</sup><br><350 | Volume mm <sup>3</sup><br>350-2000 | Volume mm <sup>3</sup><br>>2000 |
|------------------------------------------------------|--------------------------------|------------------------------------|---------------------------------|
| PB-Free Assembly   Package Thickness < 1.6 mm        | 260 °C                         | 260 °C                             | 260 °C                          |
| PB-Free Assembly   Package Thickness 1.6 mm - 2.5 mm | 260 °C                         | 250 °C                             | 245 °C                          |
| PB-Free Assembly   Package Thickness > 2.5 mm        | 250 °C                         | 245 °C                             | 245 °C                          |

refer to IPC/ JEDEC J-STD-020E

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |  |                |                         |                                 |                                  |                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------|-------------------------|---------------------------------|----------------------------------|---------------------------------------------------------------------------------------------------------------|
| <div><div></div><div><div><div>WURTH<br/>ELEKTRONIK</div><div>MORE THAN<br/>YOU EXPECT</div></div></div><div><div>Wurth Electronics Midcom Inc. Headquarters<br/>121 Airport Drive<br/>57201 Watertown, SD<br/>United States<br/>Phone: +1 (605) 886-4385<br/>www.we-online.com/midcom<br/>midcom@we-online.com</div></div></div> |  | CHECKED<br>EOI | REVISION<br>001.001     | DATE (YYYY-MM-DD)<br>2026-07-17 | GENERAL TOLERANCE<br>ISO 2768-1m | PROJECTION<br>METHOD<br> |
| DESCRIPTION<br><b>WE-AGDT Auxiliary Gate Drive Transformer</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |                |                         |                                 | ORDER CODE<br><b>750319917</b>   |                                                                                                               |
| SIZE/TYPE<br>2015                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |                | BUSINESS UNIT<br>Midcom | STATUS<br>Valid                 | PAGE<br>5/8                      |                                                                                                               |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos Group products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos Group must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Further information

Component Libraries:


|             |                                                    |
|-------------|----------------------------------------------------|
| 3D          | <a href="#">3D PDF for WE-AGDT-2015 (250-1281)</a> |
| Altium      | <a href="#">Altium_WE-AGDT (26a)</a>               |
| Cadence17-2 | <a href="#">Cadence_WE-AGDT (26a)</a>              |
| Eagle       | <a href="#">Eagle_WE-AGDT (26a)</a>                |
| IGS         | <a href="#">Downloads_IGS_WE-AGDT_2015</a>         |
| KiCad       | <a href="#">KiCad_WE-AGDT (26c)</a>                |
| LTSpice     | <a href="#">LTSpice_WE-AGDT (26a)</a>              |
| PSpice      | <a href="#">PSpice_WE-AGDT (26a)</a>               |
| STP         | <a href="#">Header_250-1281</a>                    |

Free Sample Order:

[Order free samples of this article directly here!](#)

Tutorials:

- [Drive hard. Drive safe. WE-AGDT Gate Drive Transformer \(PDF\)](#)
- [Full bridge isolated gate driver supply - with dual output peak rectification for SiC](#)
- [Full bridge isolated gate driver supply - with dual output voltage doubler for IGBT](#)
- [Full bridge isolated gate driver supply - with dual output peak rectification](#)
- [Isolated SiC & IGBT gate-drive reference design with integrated switch PSR flyback converter](#)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                |                         |                                 |                                  |                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|-------------------------|---------------------------------|----------------------------------|---------------------------------------------------------------------------------------------------------------|
| <div><div><div>RoHS<br/>COMPLIANT</div></div><div><div>REACH<br/>COMPLIANT</div></div><div><div>HALOGEN<br/>FREE</div></div><div><div>AEC<br/>Q200</div></div></div> | CHECKED<br>EOI                                                 | REVISION<br>001.001     | DATE (YYYY-MM-DD)<br>2026-07-17 | GENERAL TOLERANCE<br>ISO 2768-1m | PROJECTION<br>METHOD<br> |
| <div><div><div>WURTH<br/>ELEKTRONIK<br/>MORE THAN<br/>YOU EXPECT</div></div><div><div>Wurth Electronics Midcom Inc. Headquarters<br/>121 Airport Drive<br/>57201 Watertown, SD<br/>United States<br/>Phone: +1 (605) 886-4385<br/><a href="http://www.we-online.com/midcom">www.we-online.com/midcom</a><br/><a href="mailto:midcom@we-online.com">midcom@we-online.com</a></div></div></div>                                    | DESCRIPTION<br><b>WE-AGDT Auxiliary Gate Drive Transformer</b> |                         | ORDER CODE<br><b>750319917</b>  |                                  |                                                                                                               |
| SIZE/TYPE<br>2015                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                | BUSINESS UNIT<br>Midcom | STATUS<br>Valid                 | PAGE<br>6/8                      |                                                                                                               |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos Group products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos Group must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

## Cautions and Warnings:

The following conditions apply to all goods within the product series of WE-AGDT of Würth Elektronik eiSos GmbH & Co. KG:

### General:

- This electronic component is designed and manufactured for use in general electronic equipment.
- Würth Elektronik must be asked for written approval (following the PPAP procedure) before incorporating the components into any equipment in fields such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required and/or if there is the possibility of direct damage or human injury.
- Electronic components that will be used in safety-critical or high-reliability applications, should be pre-evaluated by the customer.
- The component is designed and manufactured to be used within the datasheet specified values. If the usage and operation conditions specified in the datasheet are not met, the wire insulation may be damaged or dissolved.
- Do not drop or impact the components, as the component may be damaged.
- Würth Elektronik products are qualified according to international standards, which are listed in each product reliability report. Würth Elektronik does not warrant any customer qualified product characteristics beyond Würth Elektronik's specifications, for its validity and sustainability over time.
- The responsibility for the applicability of the customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products also apply to customer specific products.

### Product specific:

### Soldering:

- The solder profile must comply with the technical product specifications. All other profiles will void the warranty.
- All other soldering methods are at the customers' own risk.
- Strong forces which may affect the coplanarity of the components' electrical connection with the PCB (i.e. pins), can damage the component, resulting in avoid of the warranty.

### Cleaning and Washing:

- Washing agents used during the production to clean the customer application might damage or change the characteristics of the wire insulation, marking or plating. Washing agents may have a negative effect on the long-term functionality of the product.
- Using a brush during the cleaning process may break the wire due to its small diameter. Therefore, we do not recommend using a brush during the PCB cleaning process.

### Potting:

- If the product is potted in the customer application, the potting material might shrink or expand during and after hardening. Shrinking could lead to an incomplete seal, allowing contaminants into the core. Expansion could damage the component. We recommend a manual inspection after potting to avoid these effects.

### Storage Conditions:

- A storage of Würth Elektronik products for longer than 12 months is not recommended. Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- Do not expose the components to direct sunlight.
- The storage conditions in the original packaging are defined according to DIN EN 61760-2.
- The storage conditions stated in the original packaging apply to the storage time and not to the transportation time of the components.

### Packaging:

- The packaging specifications apply only to purchase orders comprising whole packaging units. If the ordered quantity exceeds or is lower than the specified packaging unit, packaging in accordance with the packaging specifications cannot be ensured.

### Handling:

- Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty.
- Applying currents with audio-frequency signals may result in audible noise due to the magnetostrictive material properties.
- Due to heavy weight of the components, strong forces and high accelerations may have the effect to damage the electrical connection or to harm the circuit board and will void the warranty.
- The temperature rise of the component must be taken into consideration. The operating temperature is comprised of ambient temperature and temperature rise of the component. The operating temperature of the component shall not exceed the maximum temperature specified.

These cautions and warnings comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable. However, no responsibility is assumed for inaccuracies or incompleteness.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  |                                                                |                         |                                 |                                  |                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------|-------------------------|---------------------------------|----------------------------------|------------------------------------------------------------------------------------------------------------|
| <div><div><div>RoHS<br/>COMPLIANT</div></div><div><div>REACH<br/>COMPLIANT</div></div><div><div>HALOGEN<br/>FREE</div></div><div><div>AEC<br/>Q200<br/>125 °C<br/>GRADE 1</div></div></div> |  | CHECKED<br>EOI                                                 | REVISION<br>001.001     | DATE (YYYY-MM-DD)<br>2026-07-17 | GENERAL TOLERANCE<br>ISO 2768-1m | PROJECTION METHOD<br> |
| <div><div><b>WÜRTH ELEKTRONIK</b><br/>MORE THAN<br/>YOU EXPECT</div></div> <div><div>Würth Electronics Midcom Inc. Headquarters<br/>121 Airport Drive<br/>57201 Watertown, SD<br/>United States<br/>Phone: +1 (605) 886-4385<br/><a href="http://www.we-online.com/midcom">www.we-online.com/midcom</a><br/><a href="mailto:midcom@we-online.com">midcom@we-online.com</a></div></div>                                                                  |  | DESCRIPTION<br><b>WE-AGDT Auxiliary Gate Drive Transformer</b> |                         |                                 | ORDER CODE<br><b>750319917</b>   |                                                                                                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  | SIZE/TYPE<br>2015                                              | BUSINESS UNIT<br>Midcom | STATUS<br>Valid                 | PAGE<br>7/8                      |                                                                                                            |

## Important Notes

The following conditions apply to all goods within the product range of Würth Elektronik eiSos Group

### 1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos Group contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

### 2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at [www.we-online.com](http://www.we-online.com).

### 3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

### 4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

### 5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

### 6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

### 7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos Group on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos Group. Würth Elektronik eiSos Group does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos Group components or services are used.

### 8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the “General Terms and Conditions of Würth Elektronik eiSos Group”, last version available at [www.we-online.com](http://www.we-online.com).

|                                                                                                                                                                                                                                                                                                                                                    |  |                                                                |                     |                                 |                                  |                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------|---------------------|---------------------------------|----------------------------------|------------------------------------------------------------------------------------------------------------|
|     |  | CHECKED<br>EOI                                                 | REVISION<br>001.001 | DATE (YYYY-MM-DD)<br>2026-07-17 | GENERAL TOLERANCE<br>ISO 2768-1m | PROJECTION METHOD<br> |
|  <b>WÜRTH ELEKTRONIK</b><br>MORE THAN YOU EXPECT                                                                                                                                                                                                                |  | DESCRIPTION<br><b>WE-AGDT Auxiliary Gate Drive Transformer</b> |                     |                                 |                                  | ORDER CODE<br><b>750319917</b>                                                                             |
|                                                                                                                                                                                                                                                                                                                                                    |  | SIZE/TYPE<br>2015                                              |                     | BUSINESS UNIT<br>Midcom         | STATUS<br>Valid                  | PAGE<br>8/8                                                                                                |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos Group products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos Group must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.