

CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes





ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER		TEST CONDITIONS	VALUE
D.C. RESISTANCE	2-1	@20°C	6.590 ohms max.
D.C. RESISTANCE	3-5	@20°C	0.280 ohms max.
D.C. RESISTANCE	9-8	@20°C	0.270 ohms max.
INDUCTANCE	2-1	10kHz, 100mVAC, Ls	2500.0uH ±10%
LEAKAGE INDUCTANCE	2-1	tie(3+4+5+8+9), 100kHz, 100mVAC, Ls	60uH max.
DIELECTRIC	1-9	tie(2+3), 3750VAC, 1 second	3000VAC, 1 minute
DIELECTRIC	9-Core	3750VAC, 1 second	3000VAC, 1 minute
URNS RATIO		(2-1):(3-5)	8:1, ±2%
URNS RATIO		(2-1):(4-5)	22:1, ±2%
URNS RATIO		(2-1):(9-8)	8:1, ±2%

GENERAL SPECIFICATIONS:
OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC60950-1, EN60950-1, UL60950-1/CSA60950-1 and AS/NZS60950.1:
- Reinforced insulation.



Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications	CONVENTION PLACEMENT	Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 Footprint: ±.001 This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	DRAWING TITLE TRANSFORMER eiSos p/n: 750343140	PART NO. 750343140
		Method: Tray PKG-0995 www.we-online.com/midcom				
6A	6/16	SEE REVISION SHEET FOR REVISION LEVEL				SPECIFICATION SHEET 1 OF 1

