



#	Layer	Thickness	Description	Dk	Df	Note
	Top Solder	0.015mm	Soldermask IPC-SM840	3,5	0,028	used on rigid parts
1	Top Side	0.025mm	Starting foil 1/4oz. after plating and processing			
		0.030mm	Prepreg IPC-4101/127/128	3,86	0,013	FR-4.1 filled, halogen free
2	Inner Layer 1	0.025mm	Starting foil 1/4oz. after plating and processing			
		0.100mm	Core IPC-4101/127/128	3,8	0,011	FR-4.1 filled, halogen free
3	Inner Layer 2	0.025mm	Starting foil 1/4oz. after plating and processing			
		0.030mm	Prepreg IPC-4101/127/128	3,86	0,013	FR-4.1 filled, halogen free
4	Bottom Side	0.025mm	Starting foil 1/4oz. after plating and processing			
	Bottom Solder	0.015mm	Soldermask IPC-SM840	3,5	0,028	used on rigid parts

Total thickness: 0.290mm

notes:
Standard: NO PTHs.
With PTH copper 35µm on Top/Bottom

Final copper thickness according to IPC-6012

Please regard to our sectional design rules:
 ► www.we-online.com/SLIM.hdi

HDI4_1-(2b)-1_0,29_25_V2.12			
PCB Thickness Tolerance: ± 10%			
customer		created	
pcb name		approved	
engineer		format	A4, landscape
date			
Template Revision: 11/2022 by Andreas Schilpp / Michael Kress / Werner Öchslen			



**WÜRTH
ELEKTRONIK**
 MORE THAN
 YOU EXPECT