	1		2		3	4	5		T
	g,g				4.8 2.8x1.7	TECHNICAL CHARACT MATERIAL INSULATOR: PA 66 FLAMMABILITY RATIN COLOR: GREEN METAL HOUSING: BRA TERMINAL SCREW: ST TERMINAL SCREW: ST WIRE GUARD: PhBz TI FLANGES SCREW: ST ENVIRONMENTAL OPERATING TEMPERA COMPLIANCE: LEAD F ELECTRICAL CURRENT RATING: WORKING VOLTAGE: WITHSTANDING VOLTA CONTACT RESISTANC STANDARD Mus CERTIFIED E315 ▲ CERTIFIED 40023 MECHANICAL SOLID WIRE: STRANDED WIRE:	ERISTICS G: UL94-V0 SS (CuZn) 'EEL ZINC PLATING DT TYPE: "-" N PLATED EEL M2.5 TURE: -40 UP TO 105°C REE AND ROHS CULus VDE 8A 10A 300 VAC 300 VAC AGE: 1.6 KV 2.5 KV E: 20 mOhm max 414 402 26-16 AWG / 0.129-1.31 MM 26-16 AWG / 0.129-1.31 MM 1.7 Lb-In / 0.2 Nm		
	oHS Compliant					1 -			
G F			PROJE		GENERAL TOLERANCE $.X = ^{+}/_{-} 0.2$				
E				\ominus	.XX = ⁺ /_ 0.15				
D	01-APR-16	DRAWING	AK						
С	21-OCT-09	SCREW		VAL: FBr	UNIT: MM	DESCRIPTION: SERIE 3651 - 3.5MM HORIZO	NTAL CABLE ENTRY PLUG WITH	SIZE	1
C I		STANDARD	JP		SCALE:	HOOK ON WIRE SIDE - WR-TBL			
В	12-OCT-09	01/11/0/11/0							- H.
	12-OCT-09 31-OCT-08	PDF	JP		SHEET: 1/2	WERI PART NO: 691 365 110 0xx		A4	

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	oHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE]
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĬK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	lD
В]	SCALE:			٢
A	10-SEP-14	PDF	QL	1	SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			