



Order Code	ØID1 min. (mm)	ØID2 internal (mm)	t max. after shrinking (mm)	Packaging Unit (m/Reel)
71201211	1,2	0,6	0,50	150
71201611	1,6	0,8	0,55	150
71202411	2,4	1,2	0,55	150
71203211	3,2	1,6	0,55	150
71204811	4,8	2,4	0,55	75
71206411	6,4	3,2	0,65	75
71209511	9,5	4,8	0,65	75
71212711	12,7	6,4	0,65	50
71216011	16,0	8,0	0,65	50
71219011	19,0	9,5	0,80	30
71225411	25,4	12,7	0,95	30
71232011	32,0	16,0	0,95	30
71238111	38,1	19,0	1,05	30
71250811	50,8	25,4	1,14	30

Withstanding Voltage: 15 kV/mm, UL224, AC2500V, 1min
 Temperature Resistance: -55°C up to +105°C
 Shrink Temperature: min. 90°C
 Rate of shrinking: 2:1

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany com. +49 79 42 945 - 0  www.we-online.de eiSos@we-online.de	CREATED DaF	CHECKED SKI	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD 	SCALE 3 : 1
	DESCRIPTION AShST Heat Shrinking Tubes		MATERIAL Polyolefin, black		
	SIZE Type N50	WEIGHT xxx	STATUS Released	DATE 2015-08-17	BUSINESS UNIT eiCan

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.