



<b>Product / Process Change Notification (PCN)</b>																	
<input type="checkbox"/> Major Change <input checked="" type="checkbox"/> Minor Change																	
<b>PCN Number:</b> PCN_UtRJ45LAN_20240726  <b>Affected Series:</b> WE-RJ45LAN  <b>Affected Order Codes:</b> 7499xxx, Sxxx  <b>PCN Date:</b> 2024-04-26 (YYYY-MM-DD) <b>Effective Date:</b> 2024-07-26 (YYYY-MM-DD)	<b>Change Category:</b> <input type="checkbox"/> Equipment/Location <input checked="" type="checkbox"/> General Data <input type="checkbox"/> Material <input type="checkbox"/> Process <input type="checkbox"/> Product Design <input type="checkbox"/> Shipping/Packaging <input type="checkbox"/> Supplier <input type="checkbox"/> Software																
<b>Contact:</b> Product Management <b>Phone:</b> +49 (0) 7942 - 945 5001 <b>Fax:</b> +49 (0) 7942 - 945 5179 <b>E-Mail:</b> pcn.eisos@we-online.com	<b>Datasheet Change:</b> <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No  <b>Attachment:</b> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																
<b>Description of Change:</b> As a datasheet information amendment, Würth Elektronik eiSos will correct the operating temperature of the affected order codes. This is a datasheet correction only. There will be no change in form, fit, function, quality or reliability of the product.																	
<b>Details of Change:</b> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 20%;">7499010001A</td> <td style="width: 20%;">7499010121</td> <td style="width: 20%;">7499010121A</td> <td style="width: 20%;">7499010214A</td> <td style="width: 20%;">7499010218A</td> </tr> <tr> <td>74990110030</td> <td>7499011211</td> <td>7499011218A</td> <td>7499012121A</td> <td>S14100152</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 20%;"></td> <td style="width: 40%; text-align: center; color: red;"><b>Before Change</b></td> <td style="width: 40%; text-align: center; color: green;"><b>After Change</b></td> </tr> <tr> <td style="text-align: center;">Operating temperature:</td> <td style="text-align: center; color: red;">0 to +70 °C</td> <td style="text-align: center; color: green;">-40 to +85 °C</td> </tr> </table>		7499010001A	7499010121	7499010121A	7499010214A	7499010218A	74990110030	7499011211	7499011218A	7499012121A	S14100152		<b>Before Change</b>	<b>After Change</b>	Operating temperature:	0 to +70 °C	-40 to +85 °C
7499010001A	7499010121	7499010121A	7499010214A	7499010218A													
74990110030	7499011211	7499011218A	7499012121A	S14100152													
	<b>Before Change</b>	<b>After Change</b>															
Operating temperature:	0 to +70 °C	-40 to +85 °C															
<b>Reliability / Qualification of Change:</b> There will be no change of the product, therefore no additional reliability or qualification testing was performed.																	